

# ALUCLICK Technical Data

<b>BEAM WEIGHTS</b>	
Aluclick SPW207 – 50x50mm	1.11 kg/ LM
Aluclick SPW201 – 100x50mm	1.77 kg/ LM
Aluclick SPW203 – 150x50mm	2.86 kg/ LM
Aluclick SPW202 capping	0.30 kg/ LM
Aluclick SPW204 fixing	0.57 kg/ LM

<b>SPAN LIMITS</b>				
<b>Beam Type</b>	<b>Suggested span</b>	<b>Weight loading to centre of span</b>	<b>Deflection at centre</b>	<b>Maximum cantilever</b>
Aluclick SPW207 – 50x50mm	2400mm	Est. 1kg	1mm	1200mm
	2400mm	Est. 2kg	2mm	1200mm
Aluclick SPW201 – 100x50mm	3000mm	10kg	1.5mm	1500mm
	3000mm	20kg	3mm	1500mm
	6000mm	2.5kg	3mm	1500mm
	6000mm	5kg	6mm	1500mm
Aluclick SPW203 – 150x50mm	3000mm	40kg	1mm	1500mm
	3000mm	65kg	2mm	1500mm
	6000mm	20kg	2mm	1500mm
	6000mm	40kg	5mm	1500mm

Deflections above are short term deflections based on interior ceiling install. Note when installed vertically indoors, spans and cantilever distances can be doubled.

Datasheet updated 170522.