

Product Attributes Table

Standard
 Optional

Products	Applications				Fire Groups Available			Sustainable Timber				ACCESS	ACOUSTICS		
	WALLS	CEILINGS	FLOATING	SCREENS	CURVES	STANDARD LENGTHS	STANDARD WIDTHS	PEFC	FSC	LOW VOC	EO				
Panels	SUPATILE DIT		●	●		2-3	1200, 600	600, 300	○	○	●	●	100%	aw 0.75	
	SUPATILE 3D		●	●		2-3	600	600	○	○	●	●	100%	aw 0.60	
	SUPACOUSTIC	●	●	●		●	1-3	2400, 3600	600, 1200	○	○	●	●	○	aw 0.75
	SUPALINE	●	●	●		●	1-3	2400, 3600	600, 1200	○	○	●	●	○	n/a
Slats	SUPATILE SLAT		●	●		1-3	1200, 600	600, 300	○	○	●	●	100%	aw 0.75	
	SUPASLAT	●	●	●		●	1-3	2400	n/a	○	○	●	●	○	aw 0.80
	SUPASLAT ALUMINIUM	●	●	●	●		1	3200, 6400	Varies	n/a	n/a	●	n/a	○	aw 0.80
Beams	ALCLICK	●	●	●	●		1	3200, 6400	Varies	n/a	n/a	●	n/a	○	aw 0.80
	MAXI BEAM	●	●	●	●	○	2-3	up to 3600	50	○	○	●	●	○	aw 0.85
	WAVE BLADES	●	●	●	●	●	2-3	2400, 3600	18	○	○	●	●	○	aw 0.85
	WAFFLE BLADES		●	●			2-3	2400	18	○	○	●	●	○	aw 0.85