



Specification Wording

- > Ceiling feature is to be WAFFLE BLADES geometric ceilings from SUPAWOOD.
- > Blade Finish Type is to be [SUPAFINISH/ SUPAVENEER, (delete as required)] and panel finish colour is to be [.....]
- > Blade edge to be [matching edge, Natural MDF edge, (delete as required)] and to be 18mm thick.
- > Blade angle to be [60 to 90 degree intersection]. Extra diagonals required to create triangles (delete if not required).
- > Grid spacing to be [300mm to 1200mm] with grid depth to be [100mm minimum] /as shown on drawings.
- > To be supplied with [no backing/ 12mm SUPABAB acoustic backing in sheets of 2400x1200, backing in a solid or acoustic panel in finish (delete/ specify/ refer to drawings as required)], with an access option (delete if not required).
- > Blades to be supplied from the factory ready to install, any shaping etc to be done in the factory and factory finished
- > Fixing System to be concealed as per Supawood's recommendation for Waffle Blades.
- > Panels to be Fire Group 3 / 2 [delete as required] per BCA Specification C1.10 clause 4.
- > [delete this paragraph if not required] Panels are to be FSC or PEFC certified. Documentary evidence in the form of an invoice with each line item annotated with the PEFC/FSC content and supplier's chain-of-custody number must be provided to the project superintendent for project completion.
- > System as a whole is to have a minimum of 10 years warranty by the manufacturer.
Proof of validity of manufacturer's warranty is to be provided to the superintendent before practical completion.
- > Panels are to be installed in accordance with SUPAWOOD's proprietary Installation Instructions and AS/NZS 2785.
- > Installation to be done by a Supawood Certified ceiling and partition contractor.

Please contact Supawood on 1800 002 123 or info@supawood.com.au if you have any questions, queries or suggestions.